PATENT ABSTRACTS OF JAPAN

(11)Publication number:

2002-019065

(43)Date of publication of application: 22.01.2002

B32B 27/36 B32B 27/32 C08K 5/00 CO8L 21/00 CO8L 23/00 CO8L 33/06 CO8L 69/00 C08L101/00 G02B 1/04 G02B 5/02

(21)Application number: 2000-204165

(22)Date of filing:

05.07.2000

(71)Applicant: (72)Inventor:

JSP CORP

IWASAKI SATOSHI ISHIHARA YOSHIHISA MOMOSE YOSHIAKI **AOKI TAKESHI**

TAKAHASHI SEIJI

(54) RESIN MOLDING AND LIGHT REFLECTOR

PROBLEM TO BE SOLVED: To provide a resin molding having excellent heat resistance, productivity, fracture resistance and light reflecting performance and a light reflector contributing to a reduction of a power consumption when used for an electric decoration signboard or the like.

SOLUTION: The resin molding comprises a multilayer structure including a mixed resin layer containing an aromatic polycarbonate resin (A) of 35 to 75 wt.%, a thermoplastic resin or/and a thermoplastic elastomer (B) of 5 to 45 wt.% except the aromatic polycarbonate resin, and a flame retardant (C) of 0 to 35 wt.% and a white pigment (D) of 0 to 15 wt.% (wherein (A)+(B)+(C)+(D)=100 wt.%). A rear layer containing a synthetic resin or a synthetic resin composition having an Izod impact value of at least 5 kJ/m2 and is integrally adhered to the rear surface of the mixed resin layer, in such a manner that a total reflectivity of a parameter for representing a reflection of a light on the surface of the mixed resin layer is 80% or more and a diffusion reflectivity is 75% or more. The light reflector is provided as a product of the resin.

LEGAL STATUS

[Date of request for examination]

of sending the examiner's decision of rejection

[Kind of final disposal of application other than the examiner's decision of rejection or application converted registration]

[Date of final disposal for application]

[Patent number]

[Date of registration]

[Number of appeal against examiner's decision of rejection]

[Date of requesting appeal against examiner's decision of rejection]

[Date of extinction of right]

Copyright (C); 1998,2003 Japan Patent Office